PRODUCT SPECIFICATIONS

FALLTECH®

FT-X™ LEADING EDGE CABLE

Calculate Your Fall Clearance | AXIS™ By FallTech®

82808SP0

8' FT-X® Cable Class 2 Leading Edge Personal SRL-P, Single-leg with Steel Mini Rebar Hook

CONTACT SALES

Features :

- Lightest SRL in its class with less than 5 lbs. of effective weight on the back while device is in use
- Compact design elevates the SRDs to align optimally with worker motion, increasing both comfort and productivity
- Features comprehensive fall clearance charts and tables inside the energy absorber cover
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- AXIS™ enabled: Easily and accurately calculate minimum fall clearance with the AXIS safety calculator on your mobile device or computer
- Complies with ANSI Z359.14-2021 Class 2 SRL-P. Learn more and download White Paper



Material Specifications	
Cable	3/16" galvanized steel; 3,600 lb min. static strength
Energy Absorber	Polyester tear-away
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Aluminum alloy; 3,600 lb min.

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 2 SRL-P
Avg. Arrest Force	1,350 lb max.
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 420 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
CSA	Z259.2.2-2017
ANSI	Z359.14-2021