

7372

Pass-through Choker Anchor with Heavy-duty Wear Pad

Features :

- Features 1-3/4" load-bearing web with 3" wide full-length wear pad for abrasion resistance
- Appropriately sized alloy steel D-rings provide simple pass-through choke-on installation.
- May be passed-through multiple times to shorten length
- Smaller D-ring facilitates connection point for SRLs and lanyards
- Each D-ring termination features three individual 2" box-stitches for longer life
- Complies with ANSI Z359.18-2017



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-rings	Plated alloy steel; 5,000 lb min. static strength
Wear Pad	3" Polyester webbing

Performance Specifications	
Static Strength	5,000 lb min.
ANSI User Capacity	136 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.18-2017
OSHA	1926.502 and 1910.66
CSA	Z259.15-2017

Sizes & Part Numbers								
7324 - 2' (ANSI Compliant)	7336 - 3' (ANSI Compliant)	C7336 - 3' (CSA Compliant)	7348 - 4' (ANSI Compliant)	C7348 - 4' (CSA Compliant)	7372 - 6' (ANSI Compliant)	C7372 - 6' (CSA Compliant)	737208 - 8' (ANSI Compliant)	737210 - 10' (ANSI Compliant)
7373 - 12' (ANSI Compliant)	C7373 - 12' (CSA Compliant)	737214 - 14' (ANSI Compliant)	737220 - 20' (ANSI Compliant)	737224 - 24' (ANSI Compliant)	737230 - 30' (ANSI Compliant)			